

LED FLOOD LIGHTING



PRODUCT FEATURES:

- ❖ LUMILEDS LED, high luminous efficiency and long working life.
- ❖ High efficiency LED Driver, input voltage AC120-277V;
- ❖ Die-cast alloy design, better cooling, light quality, LED Tj < 85°C.
- ❖ Optical design, greatly improved the light utilization and evenness
- ❖ **Photocell Control (Optional)**

MODEL #	
PROJECT:	
NOTES:	
DATE:	
PREPARED BY:	

Additional Information:


- Power: 70W
- Input: AC 120-277V
- CCT : 5000K
- Output: 6800 LM
- Light Source: LUMILEDS
- Driver: OWN

Structure Features:

- Shell Material: Alloy & Glass
- Color: Dark Bronze
- Weight: 6 lbs.

PRODUCT APPLICATIONS:

1000LED Flood Lighting series can be widely used in Building Facades, General Area, Parking Lots and Security Lighting.





LED FLOOD LIGHTING

TECHNICAL PARAMETERS:

Type	1L-FLO7W27-XXK-Z-M		
Power	70W	Lighting Angle	101°
Input Voltage	AC120-277V	LED Brightness Decay	<5%/6000 hrs
PF	>0.95	Working Life	>50000 hrs
Driver Efficiency	>90%	Working Temperature	-30 - +45°C
Luminous Flux	6800 Lm	Storage Temperature	-40 -+80°C
Color Temperature	3000K/4000K/5000K/6500K	Protection Level	Wet Location/IP65
CRI	Ra>80	Cable	3core, 18 AWG

IRRADIATION AREA: Photometry



LED FLOOD LIGHTING

ORDERING INFORMATION:

EXAMPLE: **1L-FL 07W 27-XXK-Z-M**

1L	FL	70W	27	50K	K	P12
Company	Product	Power	Voltage	ColorTemp	Mount	Photocell
1000LED	FL Flood Light	45W (45W) 07W (70W)	27 AC120-277V	30K (3000K) 40K (4000K) 50K (5000K) 57K (5700K) ± 500K	K Knuckle T Trunnion	P12 100V Photocell P20 200V Photocell

PRODUCT CERTIFICATIONS:

